## CONTROL BEARINGS

# MODELS KP16B~KP49B MODELS B538DD~B546DD

### **KP-B SERIES**

KP-B SERIES RADIAL TORQUE TUBE TYPE	BEARING NUMBER		DIMENSIONS						LOAD RATING					
			D	d	В	С	d1	20,10		., , , , , , , ,		WEIGHT		
			inch +0.0000 -0.0010	inch +0.0007 -0.0007	inch +0.000 -0.005	inch +0.000 -0.005	inch	RADIAL		THRUST				
- c -			mm +0.000 -0.025	mm +0.018 -0.018	mm +0.00 -0.13	mm +0.00 -0.13	mm	lbs.	N	lbs.	N	lbs.	kg :	
KP K	KP16B	inch	1.7500	1.0000	0.437	0.375	1.184	8090	36000	3600	16000	0.14	0.064	
		mm	44.450	25.400	11.10	9.52	30.07							
	KP21B	inch	2.0625	1.3131	0.437	0.375	1.478	9840	43000	4400	19000	0.16	0.073	
		mm	52.388	33.350	11.10	9.52	37.54							
	KP23B	inch	2.1875	1.4380	0.437	0.375	1.605	10500	46500	4700	20800	0.17	0.077	
		mm	55.562	36.525	11.10	9.52	40.77							
	KP25B	inch	2.3125	1.5630	0.437	0.375	1.720	11300	50000	5000	22400	0.19	0.086	
		mm	58.738	39.700	11.10	9.52	43.69							
	KP29B	inch	2.5625	1.8130	0.437	0.375	1.960	12700	56000	5600	25000	0.21	0.095	
		mm	65.088	46.050	11.10	9.52	49.78							
	KP33B	inch	2.8125	2.0630	0.437	0.375	2.262	14400	64000	6400	28500	0.23	0.104	
		mm	71.438	52.400	11.10	9.52	57.46							
	KP37B	inch	3.0625	2.3130	0.437	0.375	2.500	15800	71000	7000	31000	0.26	0.118	
		mm	77.788	58.750	11.10	9.52	63.50							
	KP47B	inch	3.8750	2.9380	0.437	0.469	3.120	24700	100000	10900	48000	0.49	0.222	
		mm	98.425	74.625	11.10	11.91	79.25							
	KP49B	inch	4.0000	3.0630	0.531	0.469	3.255	27500 1	122000	12100	54000	0.53	0.240	
NOTE	111 400	mm	101.600	77.800	13.49	11.91	82.68							

#### ▶ NOTE

- 1. 단열 볼 타입 베어링입니다.
- 2. 테프론실링이 장착되어 있습니다.
- 3. 보링, 캡 , 실링을 제외한 노출된 표면은 카드뮴 도금 처리되어 있습니다.
- 4. 예비윤활이 되는 베어링입니다.
- ※ 상기 규격외 특수사양주문은 본사 기술부로 문의하시기 바랍니다.
- 1. Single row, ball bearing.
- 2. Equipped with Teflon seals.
- 3. Exposed sur faces except bore, cap, and seals are cadmium plated
- 4. Prelubricated

#### **B500DD SERIES**

B500DD SERIES	BEARING NUMBER		DIMENSIONS						LOAD RATING					
EXTRA LIGHT			D	d	В	С	d1		.07101	, , , , , , ,		WEIGHT		
TORQUE TUBE TYPE			inch +0.0000 -0.0010	inch +0.0007 -0.0007	inch +0.000 -0.005	inch +0.000 -0.005	inch	RADIAL		THRUST				
			mm +0.000 -0.025	mm +0.018 -0.018	mm +0.00 -0.13	mm +0.00 -0.13	mm	lbs.	N	lbs.	N	lbs.	kg	
d <sub>1</sub> d 0	B538DD	inch	1.0625	0.6250	0.281	0.25	0.777	3280	14600	1500	6700	0.03	0.014	
		mm	26.988	15.875	7.14	6.35	19.74							
	B539DD	inch	1.1875	0.7500	0.281	0.25	0.895	3750	16600	1700	7500	0.04	0.018	
		mm	30.162	19.050	7.14	6.35	22.73							
	B540DD	inch	1.3125	0.8750	0.281	0.25	1.016	4220	18600	1900	8500	0.05	0.023	
		mm	33.338	22.225	7.14	6.35	25.81							
	B541DD	inch	1.5000	1.0625	0.281	0.25	1.216	5000	22400	2200	9800	0.06	0.027	
		mm	38.100	26.988	7.14	6.35	30.89							
	B542DD	inch	1.7500	1.3125	0.281	0.25	1.451	5950	26500	2700	12000	0.09	0.041	
		mm	44.450	33.338	7.14	6.35	36.86							
	B543DD	inch	2.0000	1.5625	0.281	0.25	1.702	6880	30500	3200	14300	0.10	0.045	
		mm	50.800	39.688	7.14	6.35	43.23							
	B544DD	inch	2.2500	1.8125	0.281	0.25	1.970	7980	35500	3600	16000	0.11	0.050	
		mm	57.150	46.038	7.14	6.35	50.4							
	B545DD -	inch	2.6250	2.0625	0.281	0.25	2.286	9220	41500	4000	17600	0.15	0.068	
		mm	66.675	52.388	7.14	6.35	58.06							
	B546DD <b>-</b>	inch	2.8750	2.3125	0.281	0.25	2.527	10150	45500	4400	19600	0.17	0.077	
		204000	20 1000	mm	73.025	58.738	7.14	6.35	64.19	1.5700	.5500			J.17

#### ► NOTE

- 1. 초경량,단열 볼베어링입니다.
- 2. 테프론이 코팅된 glass fabric 실드입니다.
- 3. 보링, 캡 , 실링을 제외한 노출된 표면은 카드뮴 도금 처리되어 있습니다.
- 4. 예비윤활이 되는 베어링입니다.
- ※ 상기 규격외 특수사양주문은 본사 기술부로 문의하시기 바랍니다.
- 1. Extra light duty, Single row, ball bearing.
- Teflon coated glass fabric shields.
   Exposed sur faces except bore, cap, and seals are cadmium plated
- 4. Prelubricated